

G26-35



- Chromed cylinder
- Nomex ironing belts
- Double feeler thermostat
- Variable ironing speed
- Cool-down system
- Excellent finish



- Cylindre chromé
- Bandes de repassage en Nomex
- Thermostat à double sonde
- Vitesse variable
- Refroidissement automatique
- Excellente qualité de repassage



- Cilindro cromato
- Cinghie di stiratura in Nomex
- Termostato a doppia sonda
- Velocità variabile
- Raffreddamento automatico
- Finish eccellente



- Rodillo en acero cromado
- Correias de planchado en Nomex
- Termóstato electrónico con dos sondeas
- Velocidad variable
- Dispositivo "Cool-down"
- Óptima calidad de planchado



- Verchromte Zylinder
- Nomex Bügelbänder
- Thermostat mit zwei Fühlern
- Stufenlos variable Geschwindigkeit
- Abkühlung-System
- Perfekte Finish



- Rolo en aço cromado
- Correias de passagem em Nomex
- Termóstato electrónico com dois sondas
- Velocidade variável
- Dispositivo de arrefecimento "Cool-down"
- Excelente qualidade da passagem a ferro





ROLLER DIMENSIONS DIMENSIONI RULLO ZYLINDERABMESSUNGEN	2580 x Ø 325 mm	DIMENSIONS ROULEAU DIMENSIONES RODILLO DIMENSÕES ROLO
HOURLY OUTPUT (r.h. 50%) PRODUZIONE ORARIA (u.r. 50%) STUNDENLEISTUNG (RF 50%)	75 kg	PRODUCTION HORAIRE (u.r. 50%) PRODUCCIÓN HORARIA (u.r. 50%) PRODUÇÃO HORÁRIA (u.r. 50%)
THERMAL CAPACITY PORTATA TERMICA THERMISCHER FÖRDERSTROM	33,5 kW - 114306 BTU	DÉBIT THERMIQUE CAPACIDAD TÉRMICA CAPACIDADE TÉRMICA
HEATING POWER POTENZA RISCALDANTE HEIZLEISTUNG	27 kW	PUISSANCE DE CHAUFFAGE POTENCIA DE CALENTAMIENTO POTÊNCIA DE AQUECIMENTO
GAS CONNECTION COLLEGAMENTO GAS GASANSCHLUB	1/2"	CONNECTION GAZ CONEXIÓN GAS LIGAÇÃO GÁS
CONNECTIONS TENSIONE DI RETE NETZSPANNUNG	V400/3N/50Hz	TENSION DU RÉSEAU ALIMENTACIÓN DE LA RED ALIMENTAÇÃO DA REDE
MOTORS POWER POTENZA MOTORI MOTORLEISTUNG	1 kW	PUISSANCE MOTEURS POTENCIA MOTORES POTÊNCIA MOTORES
VARIABLE SPEED VELOCITÀ VARIABILE VARIABLE GESCHWINDIGKEIT	1,6 ÷ 5 m/min	VITESSE VARIABLE VELOCIDAD VARIABLE VELOCIDADE VARIÁVEL
IRONER DIMENSIONS DIMENSIONI STIRATRICE MANGELABMESSUNGEN	580 x 3140 x 1150 mm	DIMENSIONS CALANDRE DIMENSIONES CALANDRIA DIMENSÕES CALANDRA
PACKING DIMENSIONS DIMENSIONI IMBALLO VERPACKUNGSABMESSUNGEN	700 x 3240 x 1450 mm	DIMENSIONS EMBALLAGE DIMENSIONES EMBALAJE DIMENSÕES EMBALAGEM
GROSS/NET WEIGHT PESO LORDO/NETTO BRUTTO/NETTOGEWICHT	840 / 780 kg	POIDS BRUT / NET PESO BRUTO / NETO PESO BRUTO / LÍQUIDO

