



Your inhouse Laundry Partner

JLA IPSO 16, 22, 30 and 35

Free-standing, High Speed Spin Coin Operated Washers

THE PROFESSIONALS CHOICE



SPECIFICATIONS



| Details | Units | JLA 16 | JLA 22 | JLA 30 | JLA 35 |
|-----------------------------|----------------|-----------|----------|----------|----------|
| Capacity | Kg(lb) | 7.5(16) | 10(22) | 13.5(30) | 16.5(35) |
| Height | mm | 1038 | 1038 | 1202 | 1202 |
| Width | mm | 660 | 660 | 780 | 780 |
| Depth | mm | 796 | 896 | 904 | 1004 |
| Net Weight | Kg | 211 | 236 | 325 | 358 |
| Drum Volume | m ³ | 0.072 | 0.094 | 0.131 | 0.164 |
| G Force - Low/High spin | G's | 74/296 | 74/296 | 88/363 | 88/363 |
| Door Opening Dia | mm | 300 | 300 | 300 | 300 |
| Electrics - Boiler Fed | Volt/ph/Amp | 240/1/10 | 240/1/10 | 240/1/16 | 240/1/16 |
| No. of Water Connections | Cold/Hot | 2/1 | 2/1 | 2/1 | 2/1 |
| Connection Size | "BSP | 3/4 | 3/4 | 3/4 | 3/4 |
| Drain Connection (Gravity)* | mm | 80/155 | 80/155 | 80/155 | 80/155 |
| Steam Rating | Kg(lb)/cycle | 7.5(16.5) | 9.5(21) | 13.2(29) | 16.5(36) |
| Connection Size | "BSP | 3/8 | 3/8 | 3/8 | 3/8 |

All specifications subject to change without notice

*Machines are supplied as standard with 2 drain connections at 80mm and 155mm high. These are maximum heights with the levelling feet in place. If the 155mm high drain is used then it is not necessary to fit an external trap. In extreme cases optional raising legs can be supplied which will increase the height by a further 75mm or 125mm respectfully.

JLA IPSO 16, 22, 30 and 35

Free-standing, High Speed Spin Coin Operated Washers

JLA coin op washers are totally free standing and combine small cabinet size with large capacity. The machines' high speed spin ensures better extraction, cutting costs and reducing drying times by up to 35%, eliminating queues for dryers. A digital display makes for easy operation.

The Ipsos brand is an emblem of quality throughout the industry. Its coin-operated washers are reputed for excellence, and are used by over 70% of UK laundrettes.

Features

Totally free-standing

Built-in Type 'A' Air Gap

Microprocessor controlled

Two spin speeds

Information display

High build quality with stainless steel cabinet and drums

Simple to use

JLA Coin Mech

Liquid soap injection control board

Choice of two drain heights

Benefits to customer

Lower installation cost. No bolting down required.

Eliminates the risk of water contamination and fully approved for direct connection to mains water, resulting in lower installation costs.

Standard with 6 customised wash cycles to suit individual needs.

1,000rpm super spin, reduces drying time by up to 30% - saves cost, increases throughput and eliminates need for separate hydro extractor. Standard spin speed for delicates prevents creasing and fabric damage.

Shows value needed to start machine and counts down as coins are added. Displays cycle selected and minutes remaining until the end of cycle.

Clean and hygienic, robust and reliable.

Simply select cycle, insert coins to displayed value and machine will start.

Any coin any currency, the only mech you'll ever need.

Easy connection to auto-dosing pump system.

Usually no need for a raising plinth or separate trap

For further information call 0800 264667

JLA Limited Meadowcroft Lane, Ripponden, West Yorkshire HX6 4AJ T 01422 822282 F 01422 824390 email info@jla.com

www.jla.com

P/JLA16-35 Coin Op/11/04 WRAS APPROVED PRODUCT NO. 9903119