



IPSO 16, 22, 30 and 35

Free-standing, High Speed Spin Washers





SPECIFICATIONS

Details	Units	16	22	30	35
Capacity	Kg(lb)	7.5(16)	10(22)	13.5(30)	16.5(35)
Height	mm	1038	1038	1202	1202
Width	mm	660	660	780	780
Depth	mm	796	896	904	1004
Net Weight	Kg	211	236	325	358
Drum Volume	m ³	0.072	0.094	0.131	0.164
G Force - Low/High spin	G's	74/296	74/296	88/363	88/363
Door Opening Dia	mm	300	300	300	300
Electrics - 9kw Heater (1ph)	Volt/ph/Amp	240/1/45(s)	240/1/45	240/1/45	240/1/45
Electrics - 6kw Heater	Volt/ph/Amp	240/1/32	240/1/32	240/1/32	240/1/32
Electrics - Steam Heated	Volt/ph/Amp	240/1/10	240/1/10	240/1/16	240/1/16
Electrics - 12kw Heater	Volt/ph/Amp	n/a	415/3/32(s)	415/3/32(s)	415/3/32(s)
Electrics - 9kw Heater (3ph)	Volt/ph/Amp	415/3/20	415/3/20		
No. of Water Connections	Cold/Hot	2/1	2/1	2/1	2/1
Connection Size	"BSP	³ / ₄	³ / ₄	³ / ₄	³ / ₄
Drain Connection (Gravity)*	mm	80/155	80/155	80/155	80/155
Steam Rating	Kg(lb)/cycle	7.5(16.5)	9.5(21)	13.2(29)	16.5(36)
Connection Size	"BSP	³ / ₈	³ / ₈	³ / ₈	³ / ₈

(s) - Standard

All specifications subject to change without notice

*Machines are supplied as standard with 2 drain connections at 80mm and 155mm high. These are maximum heights with the levelling feet in place. If the 155mm high drain is used then it is not necessary to fit an external trap. In extreme cases optional raising legs can be supplied which will increase the height by a further 75mm or 125mm respectfully.

IPSO 16, 22, 30 and 35

Free-standing, High Speed Spin Washers

Machines in this range are ideal for the highest contamination risk sites such as hospitals, care homes, veterinary surgeries and stables. They meet NHS Guidelines HSG (95)18, Category 5 of the latest Water Regulations and comply with the National Minimum Care Standards.

Features

Built-in Type 'A' Air Gap

Microprocessor controlled

Free-standing

Two spin speeds

Information display

Two sluice programmes

High build quality with stainless steel cabinet and drums

Economy button

Simple to use

Liquid soap injection control board

Choice of two drain heights

Benefits to customer

Eliminates the risk of water contamination and fully approved for direct connection to mains water, resulting in lower installation costs.

Standard with 9 customised wash cycles to suit individual needs.

Lower installation cost. No bolting down required.

1,000rpm super spin, reduces drying time by up to 30% - saves cost, increases throughput and eliminates need for separate hydro extractor. Standard spin speed for delicates prevents creasing and fabric damage.

Displays minutes remaining until the end of cycle enabling more efficient use of staff time.

Displays cycle selected and operating temperature.

Separate programmes for both thermal and chemical disinfection depending on type of fabric being processed. Enables all laundry including heat labile fabrics to be processed without handling.

Clean and hygienic, robust and reliable.

Speeds up the wash cycle for lightly soiled garments.

There are just three stages to starting these machines: choose the appropriate wash programme, select economy button if required and push start.

Easy connection to auto-dosing pump system.

Usually no need for a raising plinth or separate trap