

Speed Queen

COIN OPERATED STACK DRYERS



Speed Queen

BUILT BETTER TO LAST LONGER

Speed Queen STACK DRYER SPECIFICATIONS

MODEL	SSE (ELECTRIC)	SSG (GAS)
Control	Electro-mechanical/Coin	Electro-mechanical/Coin
Width	683mm (26 ⁷ / ₈ "	683mm (26 ⁷ / ₈ "
Depth	711mm (28"	711mm (28"
Height	1950mm (76 ¹ / ₂ "	1950mm (76 ¹ / ₂ "
Cylinder Volume	201L (7.1cu.ft)	201L (7.1cu.ft)
Motor HP	250W (1/3HP)	250W (1/3HP)
Motor rpm	1425rpm	1425rpm
BTU (GAS heated)	N/A	7.32Kw (25,000BTU/Hr)
Type of GAS	N/A	Natural or LPG
GAS connection	N/A	3/8"NPT
Heating element (Electric)	4.8Kw (2.5Kw available at extra cost)	N/A
Air outlet DIA	102mm (4"	102mm (4"
Exhaust air flow approx	105 L/sec (220CFM)	105 L/sec (220CFM)
Max exhaust static back pressure	10mm WG (.4"WG)	10mm WG (.4"WG)
Door type	Solid	Solid
Electrical requirements	230v lph 50Hz 30A or 230v lph 50Hz 13A (2.5Kw elements)	230v lph 50Hz 10A
Colour	White	White
Net weight	111Kg (245lbs)	113Kg (250lbs)
Shipping weight	118Kg (260lbs)	123Kg (270lbs)

Distributed by:



Speed Queen
Alliance Laundry Systems

For further details refer to instructions supplied with the machine, installation specification sheets, or your Speed Queen distributor. Due to continuous product improvements, design and specifications are subject to change without notice. All Speed Queen products enjoy ISO 9001 factory certification and conform to full CE specification.

